

# **DMP Flex 350 Dual**

Dual laser metal printing, Oqton's 3DXpert® software and advanced materials



### **DMP Flex 350 Dual**

High precision, high throughput

DMP Flex 350 Dual is a mid-frame printer that offers fast build turnaround times in demanding serial production environments. It provides maximum flexibility to

switch between materials.

#### **INTEGRATED METAL PRINTING**

DMP printers, Oqton's 3DXpert software and materials are fine-tuned for process reliability and repeatability.

#### **SUPERIOR MECHANICAL PROPERTIES**

Industry's lowest O<sub>2</sub> content during builds (<25 ppm) for exceptionally high-quality parts of high chemical purity.

#### **EXTENSIVELY TESTED MATERIALS**

Thousands of hours of parameter optimization ensure predictable and repeatable print quality with a broad range of materials.

#### **EXPANDED CAPABILITIES**

Leverage supportless printing with NoSupports\* technology, as well as Hybrid Alignment\* which blends the use of subtractive and additive processes.



### Typical DMP Flex 350 Dual Applications

#### **AEROSPACE & DEFENSE**

Heat exchangers, fuel injectors, swirlers, mixers

#### **MEDICAL**

Spinal cages, tibial knees, hip cups, surgical guides

#### **TRANSPORTATION**

Conforming cooling tools, heavy duty tool inserts, structural components (e.g. brackets, drive train housings), heat exchangers, manifolds

#### **CARBON CAPTURE**

Gas contactors, heat exchangers, gas condensers

#### **SEMICONDUCTOR**

Wafer tables, fluid manifolds, linear stage coolers, showerheads, gas feeders and mixers

#### **ENERGY**

Stator vanes, impellers, turbine blades, blisks and other components

## Go Further with Direct Metal Printing

#### **UNLOCK YOUR PRODUCT'S POTENTIAL**

With complete design freedom, direct metal 3D printed parts can be stronger, lighter, longer lasting and higher performing than machined or cast assemblies. Manufacture superior performing products faster and at a lower cost compared to traditional fabrication methods.

#### **STREAMLINE SUPPLY CHAINS**

With DMP, you have complete control over your production without relying on specialty components from suppliers. Print entire assemblies on demand, with fewer components.

#### **ACCELERATE TIME-TO-MARKET**

Conduct R&D, develop prototypes and manufacture production parts all in the same system. DMP users design faster and shorten production times. Transform complex assemblies taking hundreds of hours to manufacture and assemble into a single high-value part printed in hours.

#### **INCREASE MANUFACTURING AGILITY**

Metal additive manufacturing requires no tooling. You are able to quickly update designs and change production to meet variable market demands.

<sup>\*</sup>Contact our AIG Team to learn how you can utilize NoSupports and Hybrid Alignment in your application.

# **DMP Flex 350 Dual Printer Specifications**

ingle Build Volume (X x Y x Z)  deight inclusive of build plate  ayer Thickness  Adju  Ateal alloy options for dual laser configurations:  Lase	70 nm 5 x 275 x 420 mm 82 x 10.82 x 16.54 ) ustable, minimum 5 µm, typical value erForm Ti Gr5 (A) <sup>2</sup> l	· · · ·	
Height inclusive of build plate (10.8) Ayer Thickness Adju Metal alloy options for dual laser configurations: Lase	.82 x 10.82 x 16.54 ) ustable, minimum 5 μm, typical value	· · · ·	
Metal alloy options for dual laser configurations: Lase	1 . 31	· · · ·	
3 1	erForm Ti Gr5 (A) <sup>2</sup> l	2007Form 2161 (A)3	
Lase	erForm AlSi10Mg (A) <sup>3</sup>	LaserForm 316L (A) <sup>3</sup> LaserForm CoCrF75 (A) <sup>3</sup> LaserFrom Maraging Steel (A) <sup>3</sup> Certified M789 (A) <sup>3</sup>	
Material Deposition Soft	t blade recoater		
depeatability Δx (3	$\Delta x (3\sigma) = 60 \text{um}, \Delta y (3\sigma) = 60 \text{um}, \Delta z (3\sigma) = 60 \text{um}$ 200 µm		
Minimum Feature Size 200 µ			
ypical Accuracy ± 0.1	$\pm0.1\text{-}0.2\%$ with $\pm100~\mu m$ minimum		
Build Platform Heating 250°	250°C		

SPACE REQUIREMENTS	
Dimensions, uncrated (WxDxH)	2360 x 2400 x 2870 mm (93 x 95 x 113 in) <sup>4</sup>
Weight, uncrated	Approx. 4200 kg (9240 lbs)

FACILITY REQUIREMENTS		
Electrical Requirements	400 V/15 KVA/50-60Hz/3 phase	
Compressed Air Requirements	6-10 bar	
Gas Requirements	Argon, 4-6 bar	
Water Cooling	Chiller supplied with printer	

QUALITY CONTROL	
DMP Monitoring	Optional

CONTROL SYSTEM AND SOFTWARE	
Software Tools	Oqton's 3DXpert all-in-one software solution for metal additive manufacturing
Control Software	DMP Software suite
Operating System	Windows 10 IoT Enterprise
Input Data File Formats	All CAD formats, e.g. IGES, STEP, STL, native read formats incl PMI data, all Mesh formats
Network Type and Protocol	Ethernet 1 Gbps, RJ-45 plug

ACCESSORIES	
Interchangeable Build Modules	Optional secondary Removable Print Modules (RPMs) for fast material changeover
Volume Reduction Kit on removable print module with	Optional

POWDER MANAGEMENT	
Powder Management	Optional external
Material Loading	Manual

CERTIFICATION	CE, I	NRIL			
<sup>1</sup> Maximum laser power at powder layer is typical 450W for 500W lasers	<sup>2</sup> Set up A	<sup>3</sup> Set up B	<sup>4</sup> Height exclusive of signal tower	*Only for evaluation puroposes through AIG Services in the United States	

### Metal Alloys for the DMP Series

3D Systems' broad range of ready-to-run LaserForm materials is formulated and fine-tuned specifically for 3D Systems' DMP printers to deliver high part quality and consistent part properties. 3D Systems provides a print parameter database that has been extensively developed, tested and optimized with materials in 3D Systems' part production facilities. These facilities hold the unique expertise of printing over one million challenging metal production parts in various materials year over year.



Heat exchanger with complex cooling channels in LaserForm AlSi10Mg (A)



Minireactor for scale testing built in LaserForm 17-4PH (A)



Gas burner with integrated cooling channels in LaserForm Ni718 (A)



Dental partials, copings and bridges in LaserForm CoCr (C)



High corrosion resistant impeller in LaserForm 316L (A)



Blow mold with conforming holes in LaserForm Maraging Steel (B)



Turbine vane with corrosion resistance at high temperatures in Certified HX (A)



High thermal heat transfer heat exchanger in Certified CuCr2.4 (A)



Short wavelength EMS collimator in Certified Tungsten (A)




\* Availability varies by printer model



### **PROCESS MONITORING**

Advanced manufacturing requires close monitoring of process variables. DMP Monitoring is a process monitoring and non-destructive quality control system, providing a wealth of data for informed decisions on product quality and also serving as process traceability and documentation for highly regulated industries.



#### **FASTER DATA PREPARATION AND EXCEPTIONAL BUILD OPTIMIZATION**

Oqton's 3DXpert precision metal printing software is delivered with every DMP printer. Benefit from intelligent design tools and fast build preparation, relying on the extensively tested build parameter database for your material of choice. No other software lets you localize print strategies for increased precision of metal parts.

Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use, 3D Systems makes no warranties of any type. express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.

© 2024 by 3D Systems, Inc. All rights reserved. Specifications subject to change without notice. 3D Systems, the 3D Systems logo, 3DXpert, and 3D Sprint are registered trademarks of 3D Systems, Inc.

